

# NGK Spark Plug Cross Reference Chart

PLUG SIZE	NGK	AC	ACCEL	AUTOLITE	CHAMPION	TEMPERATURE
Small plug tapered seat .460" Reach 5/8" hex standard tip	----- ----- R5673-6 R5673-7 R5673-8 R5673-9	R44T R43T ----- ----- ----- -----	566 ----- ----- 265 263 262	----- 143/144 136 135 133/134 132	----- ----- BL5/BL6 BL4 BL3 BL60	HOT ↑ COLD
Small plug tapered seat .460" Reach 5/8" hex projected tip	----- ----- R5674-6 R5674-7 R5674-8 R5674-9	R44TS R43TS 42TS 40TS/41TS ----- -----	576 ----- 274 272 ----- -----	25/26 23/24 25/13/14 12 ----- -----	RV12YC BL11Y/BL13Y BL9Y BL7Y BL62Y/BL64Y BL60Y	HOT ↑ COLD
Big plug gasket seat 3/8" reach 13/16" hex projected tip	----- R5670-5 R5670-6 R5670-7 R5670-8 R5670-9	----- 44S/45S 42S ----- ----- -----	138 137 134 133 132 -----	77/84/85 75/76/175 73/74 72 ----- -----	J14Y J12Y/J13Y J10Y/J11Y J63Y J61Y/J86Y J83Y	HOT ↑ COLD
Big plug gasket seat 3/8" reach 13/16" hex projected tip	----- R5670-5 R5670-6 R5670-7 R5670-8 R5670-9	----- 44S/45S 42S ----- ----- -----	138 137 134 133 132 -----	77/84/85 75/76/175 73/74 72 ----- -----	J14Y J12Y/J13Y J10Y/J11Y J63Y J61Y/J86Y J83Y	HOT ↑ COLD
Big plug gasket seat 3/4" reach 5/8" hex standard tip	----- ----- R5671A7 R5671A8 R5671A9 R5671A10	45XL/46XL 44N/544XL 42XL 41XL ----- -----	146 ----- 143 142 141 -----	396/397 394/395/396 393/2615 2614 2613/2594 2611/2592	N8 N5/N6 N4 N3 N2/N60 N1/N57	HOT ↑ COLD
Big plug gasket seat 3/4" reach 5/8" hex projected tip	----- ----- ----- ----- R5672A8 R5672A9	45XLS 44XLS 43XLS 42XLS 41XLS -----	117 116 114/115 113 112 111	56 55 54 53 52 51	N14Y N11Y/N12Y N9Y/N10Y N7Y/N65Y N6Y/N64Y N60Y/N63Y	HOT ↑ COLD
Small Plug, 5/8" Hex, .708" Reach Projected Tip	R5724-8 R5724-9	----- -----	----- -----	AR94 AR93	S61YC S59YC	HOT ↑ COLD

Notes: To provide additional wrench clearance on NGK gasket seat plugs, NGK has reduced the hex size from it's normal 13/16" down to 5/8"

PRICES SUBJECT TO CHANGE WITHOUT NOTICE